

► Series ALLMOVE ASH

Peristaltic Pump for high pressure application, PN 16



► Pumped Liquid

Low to highly viscous liquids, pasty, neutral or aggressive, pure or abrasive, gaseous or tending to froth, also with fibrous and solids content

► Main Fields Of Application

Sewage and environmental engineering, chemical and petrochemical industries, food and beverages industry, paper and pulp industry, soap and fats industry, dye and paint industry, plastic and ceramics industry, marine and offshore engineering, agriculture

► Performance Data

Capacity	Q	up to	60	m ³ /h
avail. suc.-pressure	ps	up to	-0,95	bar
Discharge pressure	pd	up to	16	bar
Differential pressure	pdiff	up to	16	bar
Viscosity	v	up to	100000	mm ² /s
Fluid temperature	t	up to	80	°C
Permissible solid content	-	up to	50	vol %
Grain size	gr	up to	33	mm

► Construction features

Base plate design (pump and motor mounted on a base plate)
Pedestal mounting
Dry installation
Directly coupled or belt gear or belt coupled driver
Horizontal installation
Self - priming
Dry Self - priming
Reversible pumping
Sealingless and valveless

Document free of charge by phone +49 7732 86-382 fax +49 7732 86-99382

ALLWEILER AG
PO Box 1140
D-78315 Radolfzell Germany
Phone.: +49 (0)7732 86-0
Fax: +49 (0)7732 86-436
E-mail: service@allweiler.de
Internet: <http://www.allweiler.com>